

Country of Origin : China
 Operating Temperature : 0~40 [°C]
 Dimension : 93.5 x 46 x 35.8 [mm]
 Certified AC Plugs: EU, UK, USA/Japan, Aus, Korea, Brazil, Argentina
 Efficiency level (ErP) : 
 Approvals / Marks :



Features:

Wall-mount Adapter with Exchangeable AC Plugs.	For I.T.E. use only + RoHS conform.
Wide range Input (90 ~ 264) VAC / (47 ~ 63) Hz.	
Customer can choose one or more from 7 certified plugs Wxx*(W2E, W2, W3U, W2A, W2K, W2B, W2G).	
Output connector: standard: 2.1 x 5.5 x 11mm or customer requirement.	

Specification:

	Model	Voltage DC [V]	Loading [A]	Line/Road regulation [%]	Efficiency [%]	Max. Power [W]	Ripple / Noise [mV] p-p	Connector UL approved [mm]	
ErP V.	SYS 1357-1505-Wxx*	5	0~3.00	5	>76.00	15	120	2.1x5.5x11	
	SYS 1357-1809-Wxx*	9	0~2.00	5	>80.29	18	120	2.1x5.5x11	
	SYS 1357-2412-Wxx*	12	0~2.00	5	>82.00	24	120	2.1x5.5x11	
	SYS 1357-2415-Wxx*	15	0~1.60	5	>78.60	24	150	2.1x5.5x11	
	SYS 1357-2418-Wxx*	18	0~1.33	5	>78.60	24	180	2.1x5.5x11	
	SYS 1357-2424-Wxx*	24	0~1.00	5	>82.00	24	240	2.1x5.5x11	
*Wxx	Possible to order with	Wxx =W2E--Europe W2--USA,Canada,China,Japan W3U--UK W2A--Australia W2K--Korea W2B--Brazil W2G--Argentina							
OEM production	This model is certified for Uout[V] / Pout[W] = (5, 9, 15, 18, 24)V & (5~15W, 5~18, 5~24, 5~24)W by step of 1W								
INPUT	Voltage	(90 ~ 264) VAC							
	Frequency	(47 ~ 63) Hz							
	Current	1A rms@ AC low line input and DC output full load							
	Inrush Current (cold start)	40/60Amax. @ power supply cold start, ambient temperature 25°C @115Vac/230Vac nominal AC input.							
	Leakage current	< 0.25 mA max.							
PROTECTION	Over Current	> 3.3 ~ 5.5A. The power supply will be auto recovered when over current faults remove. (Fold back)							
	Over Voltage	The power supply will not be auto recovered when faults remove 110%-150%. (Voltage limit)							
	Short Circuit	Is defined as any output impedance of less than 0.1Ω. The power supply will be auto recovered when short circuit faults remove.							
OTHERS	Efficiency (typical)	>76.0% @ full load according upon spec							
	Hold up time	10ms min At AC nominal input@ output full load							
	Standby Power	0.3W max.							
	Cooling	Free air convection							
	M.T.B.F.	50K hours full rated load operation at 25°C, according to the MIL-HDBK-217F.							
	Withstand Voltage	I/P-O/P: 3000VAC							
ENVIRONMENT	Temperature	Operating: (0 ~ 40)°C / Storage: (-20 ~ 85)°C							
	Humidity	Operating: 8% ~ 90% RH non condensing / Storage: 5% ~ 95% RH non condensing							
CONNECTION	Input	Plugs: EU, UK, US, AUS, China, Korea, Brazil, Argentina --- (exchangeable)							
	Output	Plug standard center '+' or customer requirement // Cable length 1,8m or 1,37m(5V/3A)							
SAFETY	CE,GS, UL, CB, S-Mark, PSE, FCC, CCC, VCCI, BSMI, KC, T-Mark, C-Tick, PSB, SAA/Victoria, GOST-R								
EMC	EMI	EN 55022 Class B (2006)+ A1(2007) EN 61000-3-2 (2006) + A1(2009) + A2 Class A(2009)/EN 61000-3-3 (2008)							
	EMS	EN55024(1998)+A1(2001)+A2(2003) IEC 61000-4-2 (2008) IEC 61000-4-3 (2006) + A1(2007) + A2(2010) IEC 61000-4-4 (2004) + A1(2010) IEC 61000-4-5 (2005) IEC 61000-4-6 (2008) IEC 61000-4-8 (2009) IEC 61000-4-11 (2004)							
WEIGHT	1pc	N.W.: 155 g/pc + plug							
PACKING	Box	0.53 x 0.41 x 0.46 [m]							G.W.: - kg/box
		63pcs / 1box – provide without plugs / plugs are separately							

